# Technical data sheet

### Junction box B 9 T, perforation membrane, empty, metric



**Item number: 2001853** 



The B9/T... wet-room junction box comprises two different halogen-free plastic components, 2 additional entries in base with push-through membrane

(for cable diameter up to 15 mm)

with perforation membrane (for cable diameters up to 15 mm) in the floor area.

Where cable glands are used (giving additional strain relief) there is no need to remove the membrane (this saves time). Protection rating IP67 with perforation membrane and with cable gland without the removal of the perforation membra-

Nominal voltage 400 V; nominal cross-section 4 ÷ 6 mm²

The cover is secured with 4 pre-fitted, captured quick cover fastenings (180°) and can be sealed.

The fastening holes are additionally moulded with a soft plastic component, for a 5 mm bolt diameter (75 mm spacing). Clear internal dimensions 98x98x40 B9/T M empty: 2 fixing screw caps and 1 fixing screw plug























Polypropylene

### Master data


Item number	2001853	
Туре	B9TM	
Description 1	Junction box	
Manufacturer	OBO	
Dimension	110x110x50	
Colour	Light grey; RAL 7035	
Material	Polypropylene	
Smallest sales unit	5	
Unit of quantity	Piece	
Weight	13.1 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	0,5619 kg CO2e / 1 Piece	


## **Technical data sheet**

## Junction box B 9 T, perforation membrane, empty, metric



**Item number: 2001853** 





#### **Technical data**

0

Expandable	yes		
No. of entries	9		
Type of entry	Cable/gland		
Type of entry	Cable		
Type of housing penetration	Thread and sealing membrane		
Measured insulation voltage Vi	400 V		
Cover	Not transparent		
Cover fastening	Screwed		
Entry from rear	yes		
Entries	2 additional entries in base with push-through membrane		
	(for cable diameter up to 15 mm)		
Explosion-tested version	no		
Flame-resistant	Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 750°C		
Shape	Square		
Maintain electrical functions	Without		
For Ex zone	Without		
For Ex zone gas	Without		
For Ex zone dust	Without		
Halogen-free	yes		
Clear internal dimensions	98x98x40 mm		
Max. Conductor cross-section	6 mm²		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, max.	6 mm²		
Nominal cross-section, min.	4 mm²		
Nominal voltage	400 V		
	•		

# **Technical data sheet**

# Junction box B 9 T, perforation membrane, empty, metric



**Item number: 2001853** 

Technical data		
	Sealable	yes
	Protection rating	IP67
	Permitted temperature range, max.	60 °C
	Permitted temperature range, min.	-5 °C
	Weatherproof	no