Technical data sheet

Installation frame for MT45V, terminated with protective contact socket

Item number: 7408697



Terminated installation frame with three single protective contact sockets for installation in MT45V module supports.



CE

PA

Polyamide

| B.A | | | _ | _ | 4_ |
|-----|-----|-----|-------|---|----|
| М | n s | 414 | м | ы | га |
| | | | | | |


| Item number | 7408697 |
|--|-------------------------------|
| Туре | MT45V 3 3WS V |
| Description 1 | Module support |
| Description 2 | 3x1 protective contact socket |
| Manufacturer | OBO |
| Colour | Graphite black; RAL 9011 |
| Material | Polyamide |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 30.8 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to- Gate | 0,7463 kg CO2e / 1 Piece |

Technical data sheet

Installation frame for MT45V, terminated with protective contact socket

Item number: 7408697





Technical data

| Floor plate | no |
|---|------|
| Seal installation option | no |
| Suitable for raised floor installation | yes |
| Suitable for screed-flush closed underfloor ducts | yes |
| Suitable for screed-covered underfloor ducts | yes |
| Suitable for cavity floor installation | yes |
| Suitable for underfloor ducts | yes |
| Accessory mounting type | Lock |
| Strain relief option | yes |