Technical data sheet

Trunking unit, blank, height 60-110 mm

Item number: 7424424





Ready-to-mount trunking unit with three blanking lids for cable laying, consisting of the trunking base (floor trough with side and floor covering contact profiles) and trunking lid. Floor trough with holding straps for self-contacting mounting of separating retainers. The scope of delivery contains 6 height-adjustable fixing brackets, 6 screed anchors and lid butt seals (3x for nominal trunking widths of 200 and 300) or height-adjustable lid butt supports: 3x for nominal trunking width 400 and 6x for nominal trunking widths 500 and 600. Trunking lid screwed on for delivery



St

Steel

FS

Strip galvanized

Master data

Item number	7424424	
Туре	OKA-W4006050	
Description 1	Flushfloor trunking unit	
Description 2	blank	
Manufacturer	OBO	
Dimension	2400x400x60	
Material	Steel	
Surface	Strip galvanized	
Surface standard	DIN EN 10346	
Smallest sales unit	2.4	
Unit of quantity	Metre	
Weight	1812.5 kg	
Weight unit	kg/100 m	
CO2 Footprint (GWP) Cradle-to- Gate	66,7229 kg CO2e / 1 Meter	



Technical data sheet

Trunking unit, blank, height 60-110 mm

Item number: 7424424



Technical data		
Moun	nting opening cover	no
Cover	rs	3
Numb	ber of mounting openings	0
Numb	ber of insertable partitions	2
Numb units	ber of planned flush-mount	3
Numb	ber of compartments	3 St.
Moun	nting system fastening type	Floor
Floor	plate	yes
Cover	r fastening, locking	no
	installation option	yes
Install tank	llation opening for on-floor	no
Decou	uplable	no
Suitab	ble for expansion joint	no
Mesh	n wall	no
	king height, max.	110 mm
	height, min.	60 mm
Cover	r material thickness	4
	num screed height	60
	connection opening	no
	equipotential bonding	no
	separating retainer	no
	overhang	yes
	nting opening	Without
	nt-adjustment range, max.	110 mm
	nt-adjustment range, min.	60 mm
	le cross-section	12400 mm²
	ovable cover	yes
Separ	rating retainer fastening	rasten

Lock

Separating retainer fastening Separating retainer fastening