
Technical data sheet Cross-over 110 FS





Cross-over for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 110 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used in indoor areas. Fastening material must be ordered separately.



CER

St

Steel

FS

Strip galvanized


Master data

| Item number | 7027361 |
|--|---------------------------|
| Туре | RK 150 FS |
| Description 1 | Cross over |
| Description 2 | for cable tray |
| Manufacturer | OBO |
| Dimension | 110x500 |
| Colour | zinc |
| Material | Steel |
| Surface | Strip galvanized |
| Surface standard | DIN EN 10346 |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 446.5 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to- Gate | 14,3683 kg CO2e / 1 Piece |

Technical data sheet Cross-over 110 FS



Item number: 7027361



| Width | 500 mm |
|-----------------|--------|
| Height | 110 mm |
| Plate thickness | 1 mm |
| Dimension B | 500 mm |
| Dimension R | 50 mm |

Technical data

| Connector version | Integrated connector |
|---|----------------------|
| Maintain electrical functions | no |
| Material thickness, floor plate | 1 mm |
| NATO hole pattern | no |
| Rustproof steel, pickled | no |
| Permitted temperature range, max. | 120 °C |
| Permitted temperature range, min. | -20 °C |
| Wide-span version | no |
| Type of connector, cable support system | screwed/clamped |
| Recommended quantity of bolts | 48 St. |
| Rail thickness | 1.25 mm |