

Technical data sheet


UGD250-3 for rectangular installation units, for screed height 70-125 mm

Item number: 7410079











Steel

Strip galvanized

Master data


Item number	7410079
Туре	UGD 250-3 4
Description 1	Underfloor box empty
Description 2	250-3 for GES4
Manufacturer	OBO
Dimension	410x367x70
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	594 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	13,0154 kg COe / 1 Piece

Technical data sheet

UGD250-3 for rectangular installation units, for screed height 70–125 mm



Item number: 7410079



Dimension a	201 mm	
Dimension A	367 mm	
Dimension B	410 mm	
Dimension b	201 mm	

Technical data

	<u>. </u>
Floor plate	yes
Lowerable to be flush-floor	yes
Seal installation option	yes
Installation opening for on-floor tank	no
Installation opening for flush- mount unit	Square
Decouplable	yes
Screed height, max.	125 mm
Screed height, min.	70 mm
For pipe connection	no
Suitable for screed-flush closed underfloor ducts	no
Suitable for screed-covered underfloor ducts	yes
Suitable for underfloor ducts	no
Installation space, max.	11.63 dm³
Installation space, min.	6.09 dm ³
Trunking width, max.	250 mm
Trunking width, min.	190 mm
Trunking height, max.	48 mm
Duct height, min.	28 mm
Minimum screed height	70
Nominal size	250 mm
Nominal size for device installation units	4
Height-adjustment range, max.	125 mm
Height-adjustment range, min.	70 mm
on units Height-adjustment range, max.	125 mm