


Technical data sheet

Universal anchor

Item number: 2347740



Universal nylon anchor for mounting light components on walls and ceilings. Suitable for concrete, calcareous limestone, full brick, hollow brick and porous concrete. The given load values are valid for wood screws with the specified diameter.




PA Polyamide

Master data

Item number	2347740
Type	UX 5x30
Description 1	Universal anchor
Manufacturer	OBO
Dimension	5x30
Colour	Light grey
Material	Polyamide
Smallest sales unit	100
Unit of quantity	Piece
Weight	0.041 kg
Weight unit	kg/100 pc.

Dimensions



Length	30 mm
Dimension D	5 mm
Dimension L	30 mm

Technical data sheet

Universal anchor

Item number: 2347740



Technical data

Version for	Universal anchor
Concrete Frat	300
Drill hole depth	40 mm
Suitable for fastening with cable ties	no
Suitable for gas concrete	yes
Suitable for screw diameter, max.	4 mm
Suitable for screw diameter, min.	3 mm
Suitable for hexagonal wood screw	yes
Plasterboard 12.5 mm Fempf.	100
Porous calcareous sandstone KSL12 Fempf.	300
With bolts	no
Porous concrete P4 Fempf.	150
Full brick Mz12 Frat	200