

# Technical data sheet

## Trunking, type WDK 60090

Item number: 6021913



Trunking cover and base with base perforation.  
Four cover fixing devices included.  
Lid clamp can be moved along the entire length of the trunking.



**PVC** Polyvinylchloride

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 6021913                  |
| Type                               | WDK60090CW               |
| Description 1                      | Wall trunking system     |
| Description 2                      | with base perforation    |
| Manufacturer                       | OBO                      |
| Dimension                          | 60x90x2000               |
| Colour                             | Cream; RAL 9001          |
| Material                           | Polyvinylchloride        |
| Smallest sales unit                | 24                       |
| Unit of quantity                   | Metre                    |
| Weight                             | 110 kg                   |
| Weight unit                        | kg/100 m                 |
| CO2 Footprint (GWP) Cradle-to-Gate | 1,9675 kg CO2e / 1 Meter |


# Technical data sheet

## Trunking, type WDK 60090

Item number: 6021913



### Dimensions



|        |          |
|--------|----------|
| Length | 2,000 mm |
| Width  | 90 mm    |
| Height | 60 mm    |

### Technical data

|                                                                         |                      |
|-------------------------------------------------------------------------|----------------------|
| Number of fixed partitions                                              | 0                    |
| Number of cables NYM 3 x 1.5 mm <sup>2</sup> Ø 10.5 mm (without socket) | 24                   |
| Number of cables NYM 3 x 2.5 mm <sup>2</sup> Ø 11.5 mm (without socket) | 20                   |
| Number of cables NYM 5 x 1.5 mm <sup>2</sup> Ø 12.0 mm (without socket) | 18                   |
| Number of insertable partitions                                         | 1                    |
| Version, cable trunking cover                                           | Loose                |
| Fastening type                                                          | Base perforation     |
| Maintain electrical functions                                           | no                   |
| Halogen-free                                                            | no                   |
| Cable retaining clip                                                    | yes                  |
| Duct connector                                                          | no                   |
| Delivery on a roll                                                      | no                   |
| Usable cross-section                                                    | 4236 mm <sup>2</sup> |
| Protection rating                                                       | IP30                 |
| Protective film                                                         | no                   |
| Protection rating IK code                                               | IK04                 |
| Permitted temperature range, max.                                       | 60 °C                |
| Permitted temperature range, min.                                       | -5 °C                |