Technical data sheet

CMS3518 profile rail, slot 17 mm, FT, perforated

Item number: 1104591

Central C profile rail for cable routing, in conjunction with clamp clips with a hammerhead foot. Can also be used as suspension construction for cable support systems.

17 H E30 E90

St Steel

FT Hot-dip galvanised

Master data

Item number	1104591
Type	CMS3518P0600FT
Description 1	Profile rail
Description 2	perforated, slot 17mm
Manufacturer	OBO
Dimension	600x35x18
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	10
Unit of quantity	Piece
Weight	61.74 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,3623 kg CO2e / 1 Piece

Technical data sheet

CMS3518 profile rail, slot 17 mm, FT, perforated

Item number: 1104591

Dimensions



Length	600 mm
Width	35 mm
Height	18 mm
Dimension L	600 mm

Technical data

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Maintain electrical functions	yes
Material thickness	1.75 mm
With perforation	yes
With toothing	no
Profile shape	C profile
ROHS-conformant	yes
Rustproof steel, pickled	no
Slot width	17 mm
Static value A	0.88 cm^2
Static value Iy	0.41 cm^4
Static value Iz	1.81 cm^4
Static value Wy	0.41 cm^3
Static value Wz	1.03 cm^3